

M2M Control C460

Advanced M2M and IoT Platform

The perfect balance of quality, performance, flexibility and affordability

For Professional M2M and IoT Applications

The M2M Control C460 has been designed for the most demanding M2M and industrial Internet of Things applications, which cannot be solved with simpler non-programmable devices. The Device is especially suitable for rough environments (IP65).

The C460 combines a free programmable PLC controller, a data logger with an integrated GSM/3G UMTS modem. This makes the C460 to a very powerful solution for professional industrial wireless applications.

The **M2M Control RTCU Platform** brings all the necessary tools together to develop, implement and maintain today's sophisticated M2M and industrial IoT applications.

The development task is supported by the **M2M Control IDE development environment** (IEC 61131-3) complemented by a large and comprehensive documentation and application example library.

The C460 is fully supported by the **M2M Control GPRS Gateway**. The cornerstone of the communication infrastructure ensuring reliable two-way device communication in any network environment. Deploying and maintaining new application and firmware versions for devices in the field are handled by the powerful **M2M Control Upgrade & Deployment Server** (FOTA).

10 years of experience and know-how in one product!

Experience and Know-how

For 10 years Infranet Technologies has been committed to offer the most sophisticated platform for advanced and highly demanding M2M / IoT applications. We supply our products under the brand "M2M Control".

The M2M Control C460 is the result of this accumulated experience combined with valuable feedback from hundreds of professional and mission critical applications by major organizations around the world.

M2M Control products are deployed all over the world - In any imaginable application and environment.



Device Advantages

- 3G HSDPA / UMTS GSM engine.
- Internal and external antenna.
- On-Board Ethernet interface
- Digital and analog inputs
- AC/DC relay outputs (5A)
- Multiple RS232 / RS485 interfaces
- MODBUS expandable I/O
- 1-Wire Bus
- ISM medium range RF (868 Mhz)
- Digitized voice playback.
- DTMF decoding/transmission.
- Large memory capacity.
- Micro SD-Card (up to 32 GB)
- FAT32 file-system.
- AC / DC powered
- High-capacity backup battery.

Platform Advantages

- X32 execution architecture.
- RTCU IDE development tool.
- Programmable in IEC61131-3 (ST)
- Huge standard API.
- Comprehensive protocol support: TCP/IP, UDP, FTP, SMTP, MQTT and more.
- Full featured Device Simulator.
- Sophisticated deployment tools.
- Fast and free email support.
- Backward and forward compatible.

M2M Control C460 Specifications

Processor and Main-memory

- Powerful 32-bit ST ARM processor.
- 1088 KB fast execution RAM.
- 2304 KB Flash for firmware/application.
- Real-Time clock with battery backup

Storage

- 3.5 MB persistent data flash.
- 4 MB internal FAT32 flash drive.
- 1 MB circular automatic datalogger.
- 8 KB FRAM with fast access / unlimited write endurance.
- Micro SD-CARD reader. Up to 32 GB.

GSM

- 3G / HSDPA with up to 3.6 Mbps
- UMTS / EDGE / GPRS Support
- CSD with up to 19 Kbps.
- SMS / PDU.
- DTMF decoding / transmission.
- Digitized voice playback / IVR.
- eCall Accident / Emergency services
- Micro-SIM 1.8/3 volt.
- Internal SIM card-reader.
- External or internal antenna. Selectable by DIP switch or application
- Optional Gemalto SIM Chip.

User Interface

- 4 x bi-colour LED.
- DIP-switches.
- Reset / recovery switch.
- Antenna selection DIP
- Mini USB-B as service port

Electrical Specification.

- Supply voltage range: 8 to 36 VDC or 85 to 265 VAC
- Short and reverse power protected.

Battery and Charger

- On-board 2Ah (nominal) Li-Ion battery.
- Intelligent charger with temperature throttle and sub-zero degrees support.

Digital/Analog Interface

- 4x relay output.
Max. 5A @250VAC / 30VDC
- 5 x digital inputs.
Logic high: 6 to 40 VDC.
Logic low: -5 to 3 VDC.
- 4 configurable as IEC62053-31 Class A input
- Digital input #5 can be used as ignition.
- 4x analog inputs.
Range is 0..10V or 0..20mA
Resolution: 10/ 12 bit
Precision: $\pm 1.5\%$ FSR @ 25°C
- 4x analog outputs.
Range is 0..10V or 0..20mA
Resolution: 10 bit
Precision: $\pm 1.5\%$ FSR @ 25°C
- Protected against transients and low-pass filtered.
- Expandable I/O with MODBUS.

Communication

- 10BASE-T Ethernet Interface
- 1 x RS232 with control signals.
- 1 x shared RS232 / RS485
- 1 x RS485 with MODBUS support.
- 1-Wire bus.
- On-board 868 Mhz ISM RF
- ISM RF can be disabled for worldwide

Power Management

- 5 execution speeds.
- Wait for Event: Timer, Digital input, RS232, GSM and power change state.
- Wait for event, from: 600 uA@12V.
- Supervision of supply voltage.

Internal Interfaces.

- Screw-terminals for: Power, I/O and 12/24V DCOUT
- Angeled screw-terminals for: RS232, RS485, 1-Wire and 3.3V DCOUT.
- RJ45 Ethernet Connector
- Mini USB-B for programming / service

External Interfaces.

- SMA Female connector for external GSM antenna
- 3 x PG11 cable glands
- 2 x PG9 blind plugs

Physical Characteristics

- Encapsulation: Durable Polycarbonate housing.
- Approx. 680 gram without accessories.
- W 130x H 180 x D 60 mm.
(without SMA antenna and PG connectors).

Environmental Specification

- Operating temperature: -30 to 60°C.
- Battery charge temperature: -10 to 45 °C
- Recommended storage temperature: 0 to 45°C.
- Humidity: 5..90% (non condensing).
- Ingress Protection: IP65

Approvals

- CE EU EMC directive 2004/108/EU
- Applied R&TTE directive.
- GSM engine: CE/GCF/FCC/PTCRB.

Warranty

- Two-years return to factory parts and labor.
- Optional warranty up to 5 years.
(restrictions apply).

Note: Some features are currently under development.

Infranet Technologies GmbH

Tempowerkring 19
21079 Hamburg
Germany

Phone: +49 40 696 47 - 260

Telefax: +49 40 696 47 - 259

Email: sales@m2mcontrol.de

Technical support: support@m2mcontrol.de